

50X1-HUM

DATE DIST. 23 Dec 1949

NO. OF PAGES 2

SUPPLEMENT TO
REPORT NO.

SUPPLEMENT TO
REPORT NO.

LANGUAGE Russian

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF ESPIONAGE ACT 50 U. S. C. 31 AND 32 AS AMENDED. ITS TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW. REPRODUCTION OF THIS FORM IS PROHIBITED

THIS IS UNEVALUATED INFORMATION

SOURCE Mekhanizatsiya Trudovoye i Tyazhelykh Rabot, No 11, 1948.

50X1-HUM

50X1-HUM

The Makarov KM-6m Combine which is being operated in the VUGI (All-Union Coal Institute) experimental mine No 31 in the Karaganda Coal Basin differs from previous models in that the lower unit consists of the KM-1 cutting machine. Combining these units considerably increased and improved the coal-cutting capacity of the combine. A KM-4 combine, made by a plant of the Ministry of Transport-Machine Building, which was already in operation in the mine was incorporated into the KM-6m model by the mine machine shop.

The new combine weighs 9,206 kilograms. The MA-191/8m electric motor in the lower unit has an hourly capacity of 47 kilowatts. The MA-191/32 electric motors in the central and top units have an hourly capacity of 23.5 kilowatts. The conveyor is started by a 6.3-kilowatt TAG-41/5 electric motor. This combine can work a coal seam from 1.7 to 1.85 meters thick.

The combine underwent detailed testing in the mine; certain defects were discovered and eliminated. Some defects in design were noted: the design of the switch box did not assure convenient access to the fuses of the conveyor electric motor which had to be charged through two separate trapdoors. At the end of the inspection the combine was tested without load for 1 1/2 hours, and all units were found to be operating normally.

The work of the combine was observed from 29 June to 20 July 1948 and the following data was obtained: The net average time of a work cycle of the combine during the period of observation amounted to 8.1 hours or 30 percent, not counting idle periods caused by trouble with the electric motor. For one day the time was 7.5 hours or 33 percent. Average necessary loss of time was 5.8 hours or 24 percent; average unnecessary loss of time, 10.5 hours. During the period of observation the combine moved forward 1,950 linear meters and completed 16.8 work cycles. The average length of a cycle was 26 hours and 40 minutes, the longest period being 34 hours and the shortest, 18 hours. The combine mined an average of 290 meters of coal per day or 108 percent of the planned 270 meters.

5 3 2

CONFIDENTIAL

CLASSIFICATION ~~CONFIDENTIAL~~ ~~CONFIDENTIAL~~
 STATE ☒ NY ☒ NYS ☐ FBI
 COUNTY ☒ AL ☒ FB